






VersaSTUDIO BN-20

Desktop inkjet printer / cutter

Add Unlimited Value To Your Business with the Versatile VersaSTUDIO BN-20










The VersaSTUDIO BN-20 enables you to launch a stream of new businesses from your desktop. This compact professional inkjet can produce durable graphics for outdoor applications, and its Print&Cut capabilities allow you to produce labels and decals with ease. Metallic silver ink is perfect for creating striking effects, and White ink is ideal for transparent or coloured media applications. In short, the versatility of the VersaSTUDIO BN-20 adds unlimited potential to produce creative applications and add value to your business.





A Complete Solution

The BN-20 enables you to print graphics up to A2 size or 480 mm wide (18.9"), including crop marks for easy finishing. Featuring its own print management and design software, the BN-20 is a complete business solution in a box.















Roland VersaWorks Dual

Roland VersaWorks Dual Print Management Software Included

Roland VersaWorks Dual opens up a whole new world of possibilities to print businesses, with the capability to process natively both PostScript and PDF format files to streamline tasks and increase efficiency. Intricate design files with elements such as drop shadows and transparencies can be flawlessly reproduced.

Included with VersaWorks Dual is Roland DG's own Roland Color system - which features more than 1,000 spot colours and 512 metallic colours, Accurate, vibrant colour production has never been easier to achieve. Boland Texture Library also offers a full range of luxe 3D effects for users of our VersaUV printer range. VersaWorks also contains a PANTONE® spot colour matching function which automatically converts PANTONE® spot colours in your design file to a CMYK value for colour accurate output.









Summary

- · Easy-to-Use Graphical User Interface
- · Supports the last generation of Roland DG technology
- Roland Color spot colour management system, including more than 100 standard colours and 512 metallic colors (VersaSTUDIO, VersaCAMM, VSi and SOLJET XR-640)
- · Manages up to four Roland devices
- · Simultaneous RIP and print capability
- · Support for contour cutting
- · Built-in PANTONE® library automates spot color matching
- · Roland Color features more than 1,000 spot colors and 512 metallic colors that can be precisely matched using reference tools
- · Predictive ink calculator estimates the amount of ink needed for each job
- · Roland Texture Libraries for metallic and clear inks

Specifications				
Printing technology		Piezoelectric inkjet		
Media	Width	150 to 515 mm (5.9 to 20.3 in.)		
	Thistones	Maximum 1.0 mm (39 mil) with liner, for printing		
	Thickness	Maximum 0.4 mm (16 mil) with liner and 0.22 mm (9 mil) without liner, for cutting		
	Roll outer diameter	Maximum 150 mm (5.9 in.)		
	Roll weight	Maximum 6 kg (13.2 lbs.)		
	Core diameter	76.2 mm (3 in.) or 50.8 mm (2 in.)		
Printing/cutting width*1		Maximum 480 mm (18.9 in.)		
	Type and capacity	Roland ECO-SOL MAX 2 and 3 (220cc cartridges)		
Introortridges		Five colours (cyan, magenta, yellow, black, and metallic silver or white) or		
Ink cartridges	Colours	Four colours (cyan, magenta, yellow, and black)		
		(Five colours are a combination of ESL4 and ESL5)		
Printing resolution (dpi)		Maximum 1,440 dpi		
	Туре	Roland CAMM-1 series compatible		
Cutting blade	Blade offset	0.25 mm (9 mil)		
Cutting speed		10 to 150 mm/s		
Blade force		30 to 300 gf		
Software resolution (when cutting)		0.025 mm/step		
Distance accuracy (when printing) *2 *3		Error of less than ±0.3% of distance travelled, or ±0.3 mm, whichever is greater		
Distance accuracy (when cutting) *2 *4		Error of less than ±0.4% of distance travelled, or ±0.3 mm, whichever is greater		
Repetition accuracy (when cutting) *2 *5		±0.1 mm or less		
Alignment accuracy for printing and cutting *2 *6		±0.5 mm or less		
Alignment accuracy for printing and cutting		Error of less than ±0.5% of distance travelled, or		
when reloading media *2 *7		±3 mm, whichever is greater		
Print heater *8		Temperature: 35°C (95°F)		
Connectivity		USB (compliant with Universal Serial Bus Specification Revision 2.0)		
Power-saving function / Power requirements		Automatic sleep feature / AC 100 to 240 V ±10 %, 1.5 A, 50 / 60 Hz		
Power consumption	During operation	Approx. 90 W		
	Sleep mode	Approx. 5.5 W		
Acoustic noise level	During operation	62 dB (A) or less		
	During standby	42 dB (A) or less		
Dimensions / Weight		995 (W) x 585 (D) x 291 (H) mm (39.2 (W) x 23 (D) x 11.5 (H) in.) / 35 kg (79.4 lbs.)		
Environmental	Power on	Temperature: 20 to 32°C (68 to 90°F), humidity: 35 to 80%RH (no condensation)		
	Power off	Temperature: 5 to 40°C (41 to 104°F), humidity: 20 to 80%RH (no condensation)		
Included items		Power cord, USB cable, blade, blade holder, Roland Software Package,		
		Software RIP (Roland VersaWorks Dual), User's Manual, etc.		
44 To both of cities and the Friedrick of the second of th				

	ESL5-MG	Magenta, 220 cc
ECO-SOL MAX 3 Ink	ESL5-YE	Yellow, 220 cc
	ESL5-CY	Cyan, 220 cc
	ESL5-BK	Black, 220 cc
ECO SOL MAX 2 Ink	ESL4-MT	Metallic silver, 220 cc
	ESL4-WH	White, 220 cc
Cleaning liquid	SL-CL	Cleaning liquid, 1 pc.
Blade	ZEC-U5022	For thick, reflective and fluorescent vinyl, 2pcs.
Blade holder	XD-CH3	Blade holder with blade extension adjuster, made of resin

included items	Software RIP (Roland VersaWorks Dual), User's Manual, etc.		
*1 The length of printing or cutting is subject to the limitations of the program. "2 Using Roland specified media, loaded correctly, temperature: 25°C (77°F), humidity: 50 %RH, all pinch rollers are used, 25 mm or more for both right and left margins and 35 mm or more front margin, excluding expansion or contraction of			
the media, and all correction and adjustment functions of this machine have been made properly. "3 Using Roland specified media, print travel of 1m. "4 Using Roland specified media, cut travel of 1m. "5 Range for assured repetition accuracy; Length 1,000 mm "6 Provided that media length is under 1,000 mm. Excluding			
possible shift caused by expansion/contraction of the media and/or by reloading the media. *7 Using Roland specified media, data size: 1,000 mm in the media-feed			
direction, 480 mm in the carriage-movement direction. No lamination. Automatic detection of crop marks at 4 points when media is reloaded. Excludes the effects of skewed movement and of expansion and contraction of the media. *8 Warm-up is required after power up. This may require 5 to 20 minutes, depending on the			
operating environment. The preset temperature may fail to be reached 35°C (95°F) depending on the ambient temperature and media width.			



About Metallic Silver and White Inks

Due to the nature of white and silver inks, the pigment in these inks will settle in the cartridge and ink flow system, requiring you to shake the cartridge before each use. Outdoor durability is three years for CMYK inks, one year for white ink, and one to three years for metallic silver ink, depending on the media used. Roland strongly recommends lamination for both indoor and outdoor graphics to ensure the quality of metallic inks.

Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. All other trademarks are the property of their respective owners, Roland DG Corp. has licensed the MMP technology from the TPL Group.



